

Husqvarna 353 chainsaw

Contributed by David Soede
Thursday, 05 March 2009
Last Updated Thursday, 05 March 2009

Air Injection

Air Injection. Centrifugal air cleaning system for longer intervals between filter cleanings, smoother operation and reduced wear.

The two mass principle

Vibration dampening system with the handles isolated from the engine by steel springs.

Smoother operation

Rubber suspension reduces vibrations in the carburetor. Provides smoother operation and longer product life.

Three-piece crankshaft

Wrought three-piece crankshaft for maximum durability for the toughest applications.

• Low weight on all moving engine parts means fast acceleration.

• Adjustable oil pump makes it easy to set the chain lubrication according to your needs.

• Eco-pump that stops the lubrication when idling.

• Smart Start. Decompression valve for very easy starting.

• Side-mounted chain tensioner make chain adjustment quick and easy.

• Combined choke/stop control makes the saw easier to start.

• Snap off cover makes it easy to access the spark plug and air filter.

• Double acting chain brake, right hand guard and chain catcher make the saw safer to use.

• Advanced engine technology with high power, low weight and rapid acceleration for maximum performance.

• Snap-lock cylinder cover saves time when changing spark plugs and cleaning.

353 Cylinder displacement 51.7 cm³ /

3.2 cu.inch Power 2.4 kW / 3.3 hp Noise pressure 102 dB(A) Noise power 113 dB(A) Vibrations, front/rear handle 3.1 m/s² /

3.2 m/s² Weight without cutting equipment 5.0 kg / 11.0 lbs Fuel tank volume 0.50 l / 1.06 US pint Oil tank volume 0.28 l /

0.59 US pint Chain pitch .325 inch Recommended bar length 33-50 cm / 13-20 inch